



# Three environments, Ten application scenarios

Applicable Scene

### Commercial buildings: Manufacturing buildings:





Institutions:


















Schools | Applicable Ground






Government

**Affairs Centers** 







Various venues












Short pile carpet






Sandstone




| Product Advantages





Strong direct suction on floors and carpets, 15KPa super suction, dust and debris can be sucked away.



ple security guarantees.

## modes; independently take the elevator, pass the gate, and work across floors; with the all-round base station, automatic


Smart all the way

working at breakpoints;

recharging and Fill and Drain.

AI intelligent patrol inspection, continuous

Intelligently identifies hard floors and carpets and automatically switches cleaning



remote maintenance, clean data at a glance.

888888888m²


**756万份** 

Smart management

Dual-ended control

0= 168 Number o

App and cloud platform dual-end management and control, support task scheduling, temporary tasks,



ß

ß

1 5

Clear at a glance

Task scheduling

Remote maintenance

**Charging base** 

station

**4** 

Contents		Parameters
Basic info	Product size	580(L)*500(w)*600(H)mm
	Product weight	53.8kg
	Voltage	29.5V
	Noise	<75dB
Cleaning ability	Cleaning function	Mopping, Sweeping, Vacuuming, Dust-Mopping
	Mopping efficiency	350-500m²/h
	Sweeping efficiency	400-600m²/h
	Vacuuming efficiency	350-500m²/h
	Dust-Mopping efficiency	400-650m²/h
	Scrubbing width	300mm
	Cleaning width	490mm
	Maximum travel speed	0.8m/s
	Maximum climbing angle	6°
Endurance	Battery type	Ternary lithium/Lithium iron phosphate
	Battery capacity	45Ah/37.5 Ah
	Battery life	2-3.5h
	Charging time	2.5h/2h
	Clean water tank	8L
	Sewage tank	6L
	Dust bag	2L
	Product size	528(L)*300(w)*700(H)mm

Product weight

Voltage

Rated power


Maximum charging current

Operating temperature

Clean water tank

Sewage tank





25kg

AC100-240V

750w

20A

0-40°C

25L

25L